

Acromul® A640

Edition 9-2018

Acromul® A640 is a plasticizer-free aqueous copolymer emulsion based on vsm acrylic acid ester

Stabilizer: Surfactants

1. SUPPLY SPECIFICATIONS

• Solid content	60.0 ± 2.0%
• Brookfield viscosity	7,000 ± 3,000
• pH	5.0 ± 1.0

2. TYPICAL VALUES

• Minimum film-forming temperature	11.0 ± 1.0
• Prevailing particle size range	1.05 ± 0.45
• Dispersing system	anionic - non ionic
• Density at 23°C	1.06
• Mechanical stability	Excellent

APPLICATIONS

Indoor and outdoor water based paints and wall textured coatings and primers.

SPECIFIC PROPERTIES

Acromul® A640 is suitable for most interior coatings from flat to semi-gloss, textured coatings, primers and plasters with Excellent Scrub resistance, outdoor durability and easy to formulate.

PACKAGING

ACROMUL® A640 is available in bulk and in IBC's, 160kg, 150kg, 125 Kg or 50 Kg drums.

STORAGE

ACROMUL® A640 is stable for at least 12 months when stored between +5°C and +40°C.

Egyptian British Company maintains Material Safety Data sheets (MSDS) on all of its products. These contain important information that you may need to protect your employees and customers against any known health and safety hazards associated with our products. We recommend you to obtain copies of MSDS for our products, from our technical representative, and obtain copies of MSDS from your suppliers of other raw materials used with our products.