

Technical Data Sheet

Liquid Resins and Carpet Additives

SUNDRO 2105 P

Edition 12-2024

SUNDRO 2105 P IS AN AQUEOUS DISPERSION OF-PLASTICIZED POLYVINYL ACETATE EMULSION

Stabilizer: polyvinyl alcohol

SUPPLY SPECIFICATIONS

• Apperance	Milky, white viscous paste.
• polymer type	-Plasticized aqueous Poly vinyl acetate dsipersion
• Solid content	25 ± 1%
• Brookfield viscosity @ 24 °C	1,000 - 4,000 mPa.s
• pH	3 - 5

TYPICAL VALUES

• Prevailing particle size range	0.1 - 0.3 Microns
• Dispersing system	Anionic - Non-ionic
• Mechanical stability	Excellent

APPLICATIONS

SUNDRO 2105 P is Multi-purpose homopolymer, suitable for hard wood & paper adhesive.

SPECIFIC PROPERTIES

SUNDRO 2105 P is Very fine particle size, water resistance, general purpose homopolymers suitable for wood glues, paper adhesives, floor and wall cealing adhesives, and for the manufacture of water resistant emulsion putty as well.

PACKAGING

SUNDRO 2105 P is available in bulk and in 160kg, 150kg, 125 Kg or 50 Kg drums.

STORAGE

SUNDRO 2105 P is stable for at least 12 months when stored between +5°C and +40°C.

Egyptian British Company maintains Material Safety Data sheets (MSDS) on all of its products. These contain important information that you may need to protect your employees and customers against any known health and safety hazards associated with our products. We recommend you to obtain copies of MSDS for our products, from our technical representative, and obtain copies of MSDS from your suppliers of other raw materials used with our products.

All rights reserved for Egyptian-British Co.